

GY 2201PW, GY 2201PWS, GY 2201PWH

HIDROLIMPIADORA ELECTRICA

ELECTRIC HIGH PRESSURE WASHER



Ref.: GY862201, GY862201S, GY862201H

ESPECIFICACIONES TÉCNICAS TECHNICAL SPECIFICATIONS

			GY 2201PW - GY 2201PWS- GY 2201PWH
MOTOR MOTOR	Tipo	Type	Con escobillas / Brush
	Tensión (V/Hz)	Current (V/Hz)	220-240 / 50 - 120-127/60 - 220-240/60
	Potencia (Kw)	Power (Kw)	2,1
BOMBA PUMP	Presión Nominal (PSI - bar)	Rated Pressure (PSI - bar)	1740 / 120
	Presión Máxima (PSI - bar)	Max. Pressure (PSI - bar)	2465 / 170
	Caudal máximo (l/h - gph)	Maximum flow (l/h - gph)	450 - 119
	Maxima temperatura de agua (°C)	Max. Water temperature (° C)	50
	Tipo	Type	Axial en aluminio / Axial in aluminum
	Pistones	Pistons	3 en acero templado / 3 tempered steel
	Longitud manguera alta presión (m)	High pressure hose lenght (m)	5
	Longitud cable alimentacion (m)	Electric wire lenght (m)	5
ACCESORIOS ACCESSORIES	Lanza regulable	Regulable lance	Si / Yes
	Lanza turbo	Turbo lance	No
	Filtro agua	Water filter	Si / Yes
	Botella detergente	Soap bottle	Si / Yes
	Enrollador manguera	Hose reel	Si / Yes
	Cepillo fijo	Fix brush	No
	Cepillo giratorio	Rotary brush	No
EMBALAJE PACKING	Dimensiones (mm)	Dimensions (mm)	390 x 370 x 905
	Container loads (20'/40'/40HQ)	Container load (20' 40' 40HQ)	208 / 430 / 504
	EAN	EAN	8434691081581 - 8434691081598 - 8434691096486
	Peso Neto / Bruto	NW / GW	11,4 / 14,9 Kg
OTRAS CARACTERÍSTICAS OTHER SPECIFICATIONS	Ruedas de transporte	Transport wheels	
	Filtro de entrada de agua con enchufe rápido	Quick connection inlet filter	

